

## XENOL ELITE MULTI LA 5W-40 SN/CF

### Product Description and Field of Use

It is a high-performance fully synthetic engine oil developed with Low-SAPS formulation, especially for use in new generation vehicles with low emission systems (DPF, SCR). Suitable for use in gasoline, passenger diesel and light commercial vehicles.

### Properties and Benefits

- It can be used smoothly in all gasoline, passenger diesel and LPG-powered engines with natural aspiration, diesel particulate filter, pump-diesel injector, turbocharging and multi-valve engines.
- Provides unique protection against wear and corrosion thanks to its high-tech synthetic base oils and high performance additives.
- It ensures clean engines and longer component life.
- Cutting stability is available that ensures viscosity class retention.
- It helps to reduce oil consumption and wear.

### Specifications and Approvals Fulfilled

API SN/CF, ACEA C3 , MB 229.51,229.31 , GM Dexos II

### Typical Properties\*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm <sup>3</sup>	ASTM 4052	0.865
K. Viscosity, @ 100°C	cSt	ASTM D 445	12.5-16.3
Viscosity Index		ASTM D 2270	165
Flashing Point	°C	ASTM D 92	218
Pour Point	°C	ASTM D 97	-39

\* Values may vary between productions.

### Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

### Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-07