

XENOL FARM 428

Product Description and Field of Use:

It is a modern, extra high-performance, multi-purpose tractor oil. It is designed to maximize the performance of agricultural and commercial tractors operating in a wide range of environments and conditions. Recommended for service replenishment and refilling of transmissions, differentials, final drives, hydraulic and power steering systems, as well as for liquid immersed disc brakes in agricultural and industrial tractors and similar mobile equipment.

Properties and Benefits

- It has significantly increased the performance levels of heavy-duty equipment in terms of load, speed, control and reliability thanks to the new generation of technology.
- Has a high viscosity index value and contains special additives that protect the engine and extend its life.
- Prevents rust and corrosion and reduces any tendency towards cavitation, noisy pump operation and foaming that may result in increased wear.

Specifications and Approvals Fulfilled

VOLVO WB-101 , ZF TE-ML 03E , ZF TE-ML 05F , ZF TE-ML 06K , ZF TE-ML 17E , ZF TE-ML 21F , GIMA MASSEY FERGUSON CMS M1145 , AGCO Powerfluid 821 XL Allison C-4 API GL-4 CNH MAT 3505 CNH MAT 3525 CNH MAT 3540 FORD NH FNHA-2-C-201.00 Ford ESEN-M2C86-B FORD ESN-M2C134-D JICASE MS 1204 JICASE MS 1205 JICASE MS 1206 JICASE MS 1207 JICASE MS 1209 MASSEY FERGUSON CMS M1143 MASSEY FERGUSON CMS M1141 MASSEY FERGUSON CMS M1135 NEW HOLLAND WB NWH 410B Denison UTTO/THF VALTRA G2-08 CLAAS RENAULT AGRICULTURE (M1145) JCB GEAR OIL HP KUBOTA UDT Caterpillar TO-2

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.85
K. Viscosity, @ 100°C	cSt	ASTM D 445	12.5-16.3
Viscosity Index		ASTM D 2270	140
Flashing Point	°C	ASTM D 92	240
Pour Point	°C	ASTM D 97	-40

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.