

## XENOL FARM 426

### Product Description and Field of Use:

Formulated with high-quality refined paraffinic mineral oil containing extreme pressure additives and friction regulators for transmissions, final drives and hydraulic systems of farms and industrial tractors and mobile equipment, including those with oily disc brakes. Recommended for service replenishment and refilling of transmissions, differentials, final drives, hydraulic and power steering systems, as well as for liquid immersed disc brakes in agricultural and industrial tractors and similar mobile equipment.

### Properties and Benefits

- Has high heat resistance and lubricates at high temperatures. Ensures power transmission at low temperatures.
- Has a high viscosity index value and contains special additives that protect the engine and extend its life.
- Prevents rust and corrosion and reduces any tendency towards cavitation, noisy pump operation and foaming that may result in increased wear.

### Specifications and Approvals Fulfilled

JI CASE: MS 1204-MS 1205-MS 1206-MS 1207-MS 1210, JOHN DEERE: JDM J20C / J20D, NEW HOLLAND: FNHA-2-C201.00 FORD: M2C134-A/B/C/D M2C86-B/C, MASSEY FERGUSSON: M1141-M1135-M1143, WHITE FARM: Q-1826, DETROIT DIESEL ALLISON: C-3 / C-4 CATERPILLAR TO-2, VOLVO: WB-101 , API GL-4 New Holland WB NWH 410B, AGCO Powerfluid 821 XL,ZF-TE-ML 03E/05F/06K/17E/21F

### Typical Properties\*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm <sup>3</sup>	ASTM 4052	0.85
K. Viscosity, @ 100°C	cSt	ASTM D 445	9.3-12.5
Viscosity Index		ASTM D 2270	135
Flashing Point	°C	ASTM D 92	218
Pour Point	°C	ASTM D 97	-33

\* Values may vary between productions.

### Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

### Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.