



XENOL ANTIFREEZE G11 GREEN -40

It is a mono-ethylene glycol based ready to use antifreeze formulated with superior anti-corrosion, anti-wear and anti-foam additives to be used in gasoline and diesel engine coolant systems.. It is recommended to use in cold areas until -40°C. It is suitable to use in gasoline and diesel engines. It is ready to use directly. It is not recommended to use in regions colder than -40°C.

PROPERTIES

- It can be used in radiators for all seasons.
- Due to its special anticorrosion additives protects the copper and brass materials in the engine against corrosion, does not harm the seals.
- Prevents the formation of cracking and other damages caused by expansion in cold climates.
- It is compatible with all sealing components
- Nitrite, boron, phosphorus, silicate, amine free
- It is ready to use directly

SPECIFICATIONS/ APPROVALS

Technical Specifications	TEST VALUES	TEST METHOD
Appearance	Clear	-
Color	Green	ASTM D 1122
Freezing Point ©	-40	ASTM D 1177
Boiling Point ©	116	ASTM D 1120
PH Value	7.0-11.0	ASTM D 1287

* Typical values may vary slightly from production to production.

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

XENOL ENERJİ SAN. VE TİC. A.Ş.



GEBKİM ihtisas OSB Nuri Türker Caddesi No:4 Dilovası / KOCAELİ



+90 262 646 11 01



info@xenol.com



HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

XENOL ENERJİ SAN. VE TİC. A.Ş.

► GEBKİM ihtisas OSB Nuri Türker Caddesi No:4 Dilovası / KOCAELİ

☎ +90 262 646 11 01

✉ info@xenol.com