

XENOL ELITE MULTI C4 LA 5W-40 SN/CF

Product Description and Field of Use

It is a synthetic engine oil that meets the performance requirements of the new generation of engines and has been developed for use in passenger and light commercial vehicles with diesel and gasoline-powered engines.

Properties and Benefits

- Ensures maximum environmental protection by contributing to low exhaust emission levels
- Increases the efficiency and extends the life of systems that reduce exhaust gas emissions thanks to its special formula.
- Minimizes friction and ensures long life of the engine thanks to the cutting-edge additive technology.
- High Heat, Oxidation and Foam Stability: Ensures a long oil change interval while prolonging the life of the oil. Neutralizes the formed acid and protects against rust. Prevents wear with foam control.

Specifications and Approvals Fulfilled

ACEA C4-16, MB 226.51, Renault RN0720

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.865
K. Viscosity, @ 100°C	cSt	ASTM D 445	12.5-16.3
Viscosity Index		ASTM D 2270	165
Flashing Point	°C	ASTM D 92	220
Pour Point	°C	ASTM D 97	-40

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/19.07.2022-30