

XENOL ELITE MULTI 0W-40 SN/CF

Product Description and Field of Use

It is a fully synthetic engine oil that meets the highest performance level API SN class, formulated using synthetic base oils and specially selected additive technology. The new technology has been developed for use in passenger cars. It is suitable for many models with all natural aspiration, direct injection, turbocharged and multi-valve engines powered by gasoline and diesel.

Properties and Benefits

- It reduces friction even at low temperatures, improving engine performance and ensuring fuel economy thanks to its superior technology.
- It protects the engine against corrosion, and provides excellent resistance against wear.
- It creates a durable oil film in the engine at all temperatures, thus minimizing engine wear thanks to its high-viscosity index.
- It provides excellent engine protection against sediment and soot formation thanks to its superior cleaning power.

Specifications and Approvals Fulfilled

API SN/CF, ACEA A3/B4, BMW LL-98, FIAT 9.55535-M2, GM LL-B-025, MB 229.3, PORSCHE A-40, RN 0700 VW 502.00 / 505.00

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.866
K. Viscosity, @ 100°C	cSt	ASTM D 445	12.5-16.3
Viscosity Index		ASTM D 2270	165
Flashing Point	°C	ASTM D 92	225
Pour Point	°C	ASTM D 97	-41

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-13