

XENOL GENESIS MULTI 5W-30 SN/CF

Product Description and Field of Use

It is a Fully Synthetic Engine Oil specially developed for all types of vehicles with high precision. It is used to achieve the best engine performance. This low viscosity oil improves mileage and provides long engine life by preventing rust and corrosion along with its performance. The new technology has been developed for use in passenger cars. It is suitable for many models with all direct injection, turbocharged and multi-valve engines powered by gasoline and diesel.

Properties and Benefits

- Provides unique protection against wear and corrosion thanks to its high-tech synthetic base oils and high performance additives
- Provides constant lubrication in all climates and road conditions. For this reason, it can be safely used throughout all seasons, especially in winter, with excellent flow performance even at the lowest temperatures, allowing the engine to start-up easily while minimizing wear at the time of starting the engine.
- Since it has been produced with Low Friction Technology and thanks to its high viscosity index, it creates a durable oil film at every temperature, minimizing the wear that occurs during engine start-up and warm-up.
- Provides excellent protection against engine corrosion and wear.

Specifications and Approvals Fulfilled

API SN/CF, MB 229.3, VW 502 00/505 00, BMW LL-01

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.862
K. Viscosity, @ 100°C	cSt	ASTM D 445	9.8-12.5
Viscosity Index		ASTM D 2270	160
Flashing Point	°C	ASTM D 92	210
Pour Point	°C	ASTM D 97	-39

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/18.07.2022-15