

XENOL ELITE 5W-30 SL/CF

Product Description and Field of Use

Produced with specially selected synthetic base oils and additive technology, it is a fully synthetic engine oil with superior performance suitable for use in various models such as gasoline, passenger diesel and light commercial vehicles with natural aspiration, direct injection, turbocharged and multi-valve engines.

Properties and Benefits

- Ensures unmatched protection and fuel economy in all driving conditions.
- Maintains liquid state even at low temperatures, helps keep the engine clean by reducing sediment and soot formation, protects the vehicle during initial start-up and extends its service life.
- Distributes the dirt formed as a result of burning in the environment and prevents the accumulation of sediment thanks to the detergent-dispersant additives it contains. In this way, it improves engine performance and extends the life of the engine by ensuring that the lubrication ducts are constantly clean
- Provides constant lubrication in all climates and road conditions. Therefore, it can be safely used during four seasons.

Specifications and Approvals Fulfilled

API SL/CF, ACEA A3/B4, BMW LL-98, GM LL-B-025, MB 229.5, Renault RN 0710, RN 0700 VW 502.00 / 505.00

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.861
K. Viscosity, @ 100°C	cSt	ASTM D 445	9.3-12.5
Viscosity Index		ASTM D 2270	138
Flashing Point	°C	ASTM D 92	202
Pour Point	°C	ASTM D 97	-32

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-16