

XENOL ELITE MULTI FD 5W-30 SN/CF

Product Description and Field of Use

It has been developed especially for use by Ford brand vehicles which requires using engine oil at new generation Ford WSS-M2C913-D performance level. It is also suitable for all gasoline, passenger diesel and light commercial vehicles designed for use with low viscosity (HTHS) engine oil. It can also be used on Ford Transit vehicles without Diesel Particulate Filter (DPF) and without Diesel Particulate Filter (DPF) for which Ford WSSM2C913-B, C and D approvals are required.

Properties and Benefits

- Thanks to its low ash, phosphorus and sulfur content, it extends the life of exhaust emission systems and protects the environment.
- Saves fuel thanks to its low friction and oxidation performance.
- Provides superior protection with excellent flow performance on start-stop engines.
- Provides excellent protection against wear during start-up of the engine even at the lowest ambient temperatures thanks to its improved viscosity stability.
- With the help of detergent-dispersant additives in its content, it dissipates the dirt formed as a result of burning in the environment, prevents the accumulation of sludge and increases the engine performance by ensuring that the lubrication channels remain clean.
- Ensures continuous lubrication in all climates and road conditions. It makes it easy to start the engine, especially during winter.

Specifications and Approvals Fulfilled

API SN/ SL/CF, ACEA A5/B5-16, FORD WSS-M2C913-A,B,C,D, Ford 913D

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.848
K. Viscosity, @ 100°C	cSt	ASTM D 445	9.3-12.5
Viscosity Index		ASTM D 2270	158
Flashing Point	°C	ASTM D 92	202
Pour Point	°C	ASTM D 97	-39

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-14