

XENOL GENESIS MULTI 10W-40 SN/CF

Product Description and Field of Use

It is a synthetic engine oil produced to meet the lubrication needs of normal suction and turbocharged engines as a result of blending high-quality base oils and high-tech additives. It is an engine oil developed to meet the lubrication requirements of gasoline, light diesel and LPG vehicles.

Properties and Benefits

- Helps extend engine life by protecting against wear even in everyday driving conditions.
- Provides constant lubrication in all climates and road conditions.
- Can be used in gasoline, diesel and LPG compatible engines.
- Provides faster initial start-up and very fast protection.
- Saves maximum fuel and keeps the engine clean.

Specifications and Approvals Fulfilled

API SN/CF; ACEA A3/B4; MB 229,1; MB 229,3; RN0700/0710; PSA B71 2300; VW 501.00/505.00

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.87
K. Viscosity, @ 100°C	cSt	ASTM D 445	12.5-16.3
Viscosity Index		ASTM D 2270	160
Flashing Point	°C	ASTM D 92	220
Pour Point	°C	ASTM D 97	-36

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-21