

XENOL ELITE 15W-40 SL/CF

Product Description and Field of Use

It is a high-performance engine oil used in variable operating conditions in order to provide superior protection and lubrication performance in the engines produced by blending mineral base oils and special additives.

Properties and Benefits

- Complete protection against engine corrosion and wear.
- High-performance wear control with minimal sludge deposits provides fluidity over a wide temperature range.
- Formulated for all types of gasoline, diesel and LPG, naturally aspirated or turbocharged passenger and light commercial vehicle engines.

Specifications and Approvals Fulfilled

API SL/CF, ACEA A3/B3/B4

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.871
K. Viscosity, @ 100°C	cSt	ASTM D 445	12.5-16.3
Viscosity Index		ASTM D 2270	130
Flashing Point	°C	ASTM D 92	210
Pour Point	°C	ASTM D 97	-30

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/19.07.2022-24