

XENOL ELITE 20W-50 SL/CF

Product Description and Field of Use

It is a high-performance engine oil suitable for all seasons to provide superior protection and lubrication performance with high quality mineral base oils and special additive technology. It is especially suitable for use in high gasoline, LPG, passenger diesel and light commercial vehicles.

Properties and Benefits

- Helps to control sludge accumulation and deposits.
- It ensures clean engines and longer component life.
- Cutting stability is available that ensures viscosity class retention.
- It helps to reduce oil consumption and wear.
- It offers a durable oil film that provides complete lubrication in all traffic conditions and temperatures.

Specifications and Approvals Fulfilled

API SL/CF

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.891
K. Viscosity, @ 100°C	cSt	ASTM D 445	16.3-21.9
Viscosity Index		ASTM D 2270	120
Flashing Point	°C	ASTM D 92	220
Pour Point	°C	ASTM D 97	-28

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/19.07.2022-25