

## **XENOL ELITE MULTI 0W-20 SP**

### **Product Description and Field of Use**

ILSAC GF-6 is a modern fully 100% synthetic low viscosity resource conserving motor oil. The product formula has been modified in response to the higher requirements of the latest generation gasoline engines and to meet the API SP category and ILSAC GF-6 quality standard. The product exceeds General Motors dexos 1 Gen 2 requirements. It is designed for gasoline engines of passenger cars, minivans and SUVs with hybrid and traditional powertrains.

### **Properties and Benefits**

- It provides fuel economy thanks to its low viscosity feature and improved viscosity stability.
- Thanks to its superior thermal and oxidation stability, it maintains its performance during the longest oil change interval recommended by the vehicle manufacturers.
- Provides excellent protection against engine corrosion and wear.
- Provides excellent protection against wear during start-up of the engine even at the lowest ambient temperatures thanks to its improved viscosity stability.
- Manufactured with mid-SAPS (sulfated ash, phosphorus and sulfur) technology for engines with Selective Catalytic Reduction (SCR) and Diesel Particulate Filter (DPF) systems in order to reduce harmful exhaust emissions. Extends the life of the exhaust emission system and protects the environment.

### **Specifications and Approvals Fulfilled**

API SP, ILSAC GF-6, DEXOS1 GEN 2, GM 6094M, CHRYSLER MS-6395M

### **Typical Properties\***

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm <sup>3</sup>	ASTM 4052	0.831
K. Viscosity, @ 100°C	cSt	ASTM D 445	5.6-9.3
Viscosity Index		ASTM D 2270	168
Flashing Point	°C	ASTM D 92	220
Pour Point	°C	ASTM D 97	-40

\* Values may vary between productions.

### **Storage Conditions**

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

### **Health and Safety Information**

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/18.07.2022-15