

XENOL RACE 4T 10W-40 SL/CF

Product Description and Field of Use

It is a high-quality 4-stroke motorcycle oil designed for high-performance motorcycles produced by blending high quality minerals, synthetic oils and special additives.

Properties and Benefits

- Protects the engine against corrosion, oxidation, wear and foaming
- Thanks to its high viscosity index, it creates a durable oil film at every temperature, minimizing the wear that occurs during engine start-up and warm-up.
- Provides constant lubrication in all climates and road conditions. Therefore, it can be safely used during four seasons. Especially in winter, it allows the engine to start easily and minimizes wear thanks to its low viscosity.

Specifications and Approvals Fulfilled API SN/CF , JASO MA2 , API TC

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.865
K. Viscosity, @ 100°C	cSt	ASTM D 445	12.5-16.3
Viscosity Index		ASTM D 2270	140
Flashing Point	°C	ASTM D 92	221
Pour Point	°C	ASTM D 97	-36

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37