

XENOL PEARL 5W-20 SP

Product Description and Field of Use

It is a superior performance fully synthetic engine oil developed in order to provide fuel economy and long life for the engines of the new generation Japanese and Korean gasoline vehicles. It can be used smoothly in all modern technology vehicle engines with direct injection, turbocharging and multi-valve.

Properties and Benefits

- It reduces friction under all temperatures, improving engine performance and ensuring fuel economy thanks to its superior technology.
- It ensures clean engines and longer component life.
- It helps to reduce oil consumption and wear.
- It offers a durable oil film that provides complete lubrication in all traffic conditions and temperatures.
- Even at the lowest temperatures, it minimizes wear with excellent flow performance during engine start-up.
- It creates a durable oil film in the engine at all temperatures, thus minimizing engine wear thanks to its high-viscosity index.

Specifications and Approvals Fulfilled

SP/SN/SN-RC/CF,ILSAC GF-5 Dexos I Gen 2

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.850
K. Viscosity, @ 100°C	cSt	ASTM D 445	5,6- 9.3
Viscosity Index		ASTM D 2270	165
Flashing Point	°C	ASTM D 92	225
Pour Point	°C	ASTM D 97	-39

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/19.07.2022-42

XENOL/TDS/19.07.2022-42