

XENOL RACE 4T 10W-40 SN/CF

Product Description and Field of Use

High-tech, fully synthetic motorcycle oil formulated to obtain full engine performance and superior protection for all 4-stroke modern motorcycles.

Properties and Benefits

- Ensures long life of the engine and its parts thanks to its high resistance to wear, rust and corrosion.
- Provides maximum protection against wear that may occur during start-up thanks to its easy fluidity feature even at very low temperatures.
- Helps keep the engine clean and smooth by controlling the formation of deposits at high temperatures.

Specifications and Approvals Fulfilled API SN/CF , JASO MA2 , API TC

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.86
K. Viscosity, @ 100°C	cSt	ASTM D 445	12.5-16.3
Viscosity Index		ASTM D 2270	150
Flashing Point	°C	ASTM D 92	227
Pour Point	°C	ASTM D 97	-36

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37