

## XENOL LNX 7.5W-40 SN

### Product Description and Field of Use

XENOL LNX 7.5W-40 is a fully synthetic engine oil produced with an ester-based formula that provides exceptional oil film resistance at very high temperatures, developed to meet the need for long-lasting use of gasoline and diesel engine vehicles with the latest and modern technology. XENOL LNX 7.5W-40 has been developed to provide unrivaled power increase, outstanding lubrication and optimum protection against wear.

It is suitable for all high performance petrol or diesel engines, naturally aspirated or turbocharged multi-valve injection engines.

### Properties and Benefits

- It has been especially developed to provide high temperature resistance and oil pressure stability.
- It shows superior performance in variable weather conditions thanks to its high viscosity index.
- Thanks to its excellent fluidity in cold weather conditions, it provides rapid lubrication of engine parts at first start-up and protects the engine against wear.
- Thanks to the detergent and dispersant additives in its formulation, it keeps the engine parts clean.
- Thanks to its low volatility, it reduces oil consumption and thus helps to reduce hydrocarbon pollution.

### Specifications and Approvals Fulfilled

API SN/CF, ACEA A3/B4, MB 229.3, A40, VW 502 00/505 00, RN0700/0710

### Typical Properties\*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density @15 °C	g/cm <sup>3</sup>	ASTM 4052	0,865
K. Viscosity, @ 100°C	cSt	ASTM D 445	12,8-16,3
Viscosity Index		ASTM D 2270	160
Flashing Point	°C	ASTM D 92	227
TBN	mg KOH/g	ASTM D2896	8,5
Pour Point	°C	ASTM D 97	-36

\* Values may vary between productions.

### Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

XENOL/TDS/20.07.2022-18

#### Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary

XENOL/TDS/20.07.2022-18