

XENOL RACE 2T

Product Description and Field of Use

It is specially designed to provide high performance for use on motorcycles, go-karts and all other 2-stroke engines. It is used in air or water-cooled 2-stroke engines, motorcycles, flail mowers and agricultural machinery. It is recommended to use the fuel/oil ratios specified by the engine manufacturer up to a maximum of 50:1.

Properties and Benefits

- It keeps sediment formation under control and keeps the engine and its components clean thanks to the improved additives in its formulation.
- Ensures maximum protection against rust, corrosion and wear and provides longer engine life.
- Ensures effective operation of the ignition system and improves combustion efficiency.
- It can be used in oil injection systems as well as by mixing directly into fuel.

Specifications and Approvals Fulfilled

API TC; JASO FC; ISO EGC&EGD; TISI 1040

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.87
K. Viscosity, @ 100°C	cSt	ASTM D 445	10.5
Viscosity Index		ASTM D 2270	115
Flashing Point	°C	ASTM D 92	223
Pour Point	°C	ASTM D 97	-27

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37