

XENOL ATF DEXRON II

Product Description and Field of Use

Automatic transmission oil produced by blending highly refined base oils and special additives. It is used in automatic transmissions, power steering and some hydraulic systems of passenger cars and heavy vehicles.

Properties and Benefits

- Minimizes wear on automatic transmissions and improves equipment performance thanks to its special additives.
- They are long-lasting products thanks to their thermal stability and high oxidation resistance.
- Thanks to the special additives they contain, they prevent sediment formation and do not cause foaming.
- Protects the gears against rust and corrosion. Shows superior performance in hot and cold climates.

Specifications and Approvals Fulfilled

GM Dexron II-D

GM Dexron II-E

GM Type A Suffix A

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.85
K. Viscosity, @ 100°C	cSt	ASTM D 445	6.5-8
Viscosity Index		ASTM D 2270	160
Flashing Point	°C	ASTM D 92	200
Pour Point	°C	ASTM D 97	-40

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.