

XENOL ATF DEXRON VI

Product Description and Field of Use

It is a high-performance synthetic automatic transmission oil produced by blending synthetic base oils and high-tech additives. Developed for use in the next generation of transmissions of passenger and light commercial vehicles. It is especially suitable for use in automatic transmissions of new generation vehicles produced by automobile manufacturers of Far Eastern origin.

Properties and Benefits

- High performance at low temperatures thanks to its excellent viscosity.
- Thanks to its high oxidation resistance and thermal stability, it shows superior resistance to aging, ensures a long oil change period and reduces maintenance costs.
- Thanks to its special additives, it minimizes the wear that may occur in automatic gearboxes and extends the transmission life.
- Thanks to the special additives they contain, they prevent sediment formation and do not cause foaming. Provides protection against corrosion and corrosion.

Specifications and Approvals Fulfilled ALLISON C-4 ATF LT 71141 BMW / MINI P/N 83 22 2 289 720 FORD MERCON LV / P/N XT-6-QSP / DSP [SP] Chrysler / Dodge / Jeep +4 GM DEXRON VI GM DEXRON IIIH / IIIG / IIE / IID / TASA Honda DW-1 / Z-1 / ATF Type 3.0 / ATF Type 3.1 Hyundai / Kia Genuine ATF / SP-II / SP-III / SP-IV / SPH-IV / SP-IV-RR Isuzu ATF / ATF-II / ATF-III JASO M315 Class 1A Mazda FW 6A EL / FW 6AX EL / FZ / JWS 3317 / M-5 / M-III / Type- IV MB 236.5 / 6 / 7 / 8 / 9 / 10 / 11 / 12 / 41 Mitsubishi ATF-J2 / ATF-J3 / SP / SP-II / SP-III Nissan Matic Fluid D / J / K / S / W Subaru HP Suzuki 3314 / 3317 Toyota Type T / D-II / T-III / T-IV / WS (JWS 3324) Volkswagen / Audi G 060 162 (A1, A2, A6) / G 052 162 (-A1, -A2) / G 055 540 (A2) VOLVO P/N 1161521 / 1161540 / 1161640 ZF TE-ML 11A / 11B

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.85
K. Viscosity, @ 100°C	cSt	ASTM D 445	6.5
Viscosity Index		ASTM D 2270	158
Flashing Point	°C	ASTM D 92	215
Pour Point	°C	ASTM D 97	-45

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37