

XENOL HYD ATF

Product Description and Field of Use

Hydraulic steering oil obtained by blending highly refined base oils and special additives. It is designed to provide high performance in the power steering systems of passenger and heavy-duty vehicles.

Properties and Benefits

- It lubricates and protects sealing elements, hoses and metal parts, performs quietly, smoothly and fluently, and extends the life of parts.
- It is a long lasting product thanks to its thermal stability and high oxidation resistance.
- It helps to prevent leakage, noise and rust problems in the system.
- Thanks to the special additives they contain, they prevent sediment formation and do not cause foaming.
- Protects the entire system against wear, oxidation, and corrosion.

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.86
K. Viscosity, @ 100°C	cSt	ASTM D 445	6.3
Viscosity Index		ASTM D 2270	150
Flashing Point	°C	ASTM D 92	220
Pour Point	°C	ASTM D 97	-30

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37