

XENOL ATF 8-9

Product Description and Field of Use

Its superior technology provides advanced protection and a smoother ride to drivers.

Properties and Benefits

- Improved oxidation and thermal stability
- Improved friction resistance for a smoother ride for a longer time.
- Ensures fuel economy

Specifications and Approvals Fulfilled JASO M315 TYPE 1A-LV, BMW 83222289720 , HONDA 08200-9071 , HONDA ATF TYPE 3.1 , ZF AA01 500 001 , LAND ROVER OIL NO LR023288

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.85
K. Viscosity, @ 100°C	cSt	ASTM D 445	7.1
Viscosity Index		ASTM D 2270	158
Flashing Point	°C	ASTM D 92	220
Pour Point	°C	ASTM D 97	-45

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37