

XENOL ATF 220

Product Description and Field of Use

Formulated with high quality base oils and special additives to ensure proper operation of automatic transmission. Suitable for use in transmissions of truck, bus and utility machinery when required.

Properties and Benefits

- Shows resistance to varnish, mud and sludge build-up to ensure effective operation of transmissions throughout oil life
- Meets wear requirements to ensure longer transmission life
- Provides easy initial start-up and clean and fast lubrication at low ambient temperatures

Specifications and Approvals Fulfilled GM - Dexron II-D; MB 236.5; FORD - Mercon; GM - Allison C3 – C4; Caterpillar TO-2; Denison HF-0; ZF TE-ML 02F, 03D, 17C, MAN 339 TYPE V1; MAN 339 TYPE V1-Z1; Voith H55.6335.3X; ZF TE-ML 04D, 14AMAN 339 TYPE V1; MAN 339 TYPE V1-Z1; Voith H55.6335.3X; ZF TE-ML 04D, 14A

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.85
K. Viscosity, @ 100°C	cSt	ASTM D 445	7
Viscosity Index		ASTM D 2270	155
Flashing Point	°C	ASTM D 92	200
Pour Point	°C	ASTM D 97	-40

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37