

XENOL ATF LT 71141

Product Description and Field of Use

High-performance automatic transmission oil that provides long-lasting performance for use in automatic vehicle transmissions

Properties and Benefits

- Has a balanced additive performance for excellent gear shifting
- Extends transmission life
- Reduces gear friction of the outer rings, resulting in fuel economy in vehicles with automatic transmission.
- High viscosity index ensures stable viscosity over a wide range of temperature for effective protection of transmissions and operation of hydraulic steering units
- Suitable for use during 4 seasons

Specifications and Approvals Fulfilled

PEUGEOT/CITROEN AUTOMOBILES B71 2340, VOITH TURBO H55.6336.XX, ZF TE-ML 04D, ZF TE-ML 11B, ZF TE ML 14B, ZF TE-ML 17C, MB APPROVAL 236.11

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.85
K. Viscosity, @ 100°C	cSt	ASTM D 445	6.8
Viscosity Index		ASTM D 2270	170
Flashing Point	°C	ASTM D 92	200
Pour Point	°C	ASTM D 97	-36

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37