

## XENOL DSG FLUID

### Product Description and Field of Use

It is a superior performance synthetic dual-clutch transmission oil produced by blending synthetic base oils and high-tech additives. It is a high-performance synthetic wet dual-clutch transmission oil designed for use in passenger and light commercial vehicles with DSG-type transmission.

### Properties and Benefits

- Extends the life of the transmission by minimizing wear thanks to advanced additive technology.
- Creates a permanent film on metal surfaces with excellent slip stability, minimizing wear when shifting gears.
- Provides a long oil change interval and reduces maintenance costs thanks to its high oxidation resistance and thermal stability.
- Gives a smooth shifting feel in driving conditions and does not interrupt torque between gear shifts thanks to its excellent flow characteristics and high anti-wear performance.
- Contributes to fuel economy with low viscosity and low friction properties.

### Specifications and Approvals Fulfilled

BMW DCTF-1/ BMW MTF LT-5 /CHRYSLER 68044345EA /FERRARI TF DCT-F3 /FIAT 9.55550-MZ6/ FORD WSS-M2C936-A /MB 236.21 /MB 236.25 /MITSUBISHI DIAMOND QUEEN SSTF-1 /NISSAN R35 SPECIAL /PORSCHE 000.043.20 /PORSCHE 000.043.207.29/ PORSCHE 000.043.207.30 /PSA 9734 S2 /RENAULT BOT450 EDC 6-Speed/ VOLVO BOT341 #1161838 /VW G 052 182 /VW G 052 529/ VW G 052 513 /VW G 055 529/ VW TL 52182

### Typical Properties\*

| TEST                  | UNIT              | TEST METHOD | TYPICAL VALUES |
|-----------------------|-------------------|-------------|----------------|
| Density, @15 °C       | g/cm <sup>3</sup> | ASTM 4052   | 0.85           |
| K. Viscosity, @ 100°C | cSt               | ASTM D 445  | 6.8            |
| Viscosity Index       |                   | ASTM D 2270 | 170            |
| Flashing Point        | °C                | ASTM D 92   | 200            |
| Pour Point            | °C                | ASTM D 97   | -43            |

\* Values may vary between productions.

### Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

### Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37