



XENOL TRANSMISSION AHDX 75W-80

TRANSMISSION AHDX 75W-80 is high performance synthetic manuel transmission and gearbox oil which is blended by high technology synthetic base oils and additives which provide high pressure resistance, prevent oxidation of oil and protect the material against rust and prevent wear.

PROPERTIES

- Long life additives ensure long term protection of the gears and high oxidation resistance so providing extended drain capability.
- Due to the special additives it contains, it prevents the formation of residue and does not foam.
- Provides protection against rust and corrosion.
- Provides longer transmission life

SPECIFICATIONS/ APPROVALS

MAN 341 Type E4, VOLVO 97312, ZF TE-ML 02D, GL-4

TECHNICAL SPECIFICATIONS

Test	Method	Typical Properties
SAE Viscosity Grade	SAE J 306	75W-80
Kinematic Viscosity (40°C, cSt)	ASTM D445	60
Viscosity Index	ASTM D2270	150
Flash Point (°C)	ASTM D92	225
Pour Point (°C)	ASTM D97	-40
Density (20°C, g/cm3)	ASTM D 1298	0,85

*Typical values may vary slightly from production to production

STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

XENOL ENERJİ SAN. VE TİC. A.Ş.



XENOL ENERJİ SAN. VE TİC. A.Ş.

► GEBKİM ihtisas OSB Nuri Türker Caddesi No:4 Dilovası / KOCAELİ

☎ +90 262 646 11 01

✉ info@xenol.com