



XENOL SAE 15W-40 CI-4 ULTRA AVANGARDE

XENOL HILL 15W-40 CI-4 ULTRA AVANGARDE is a multigrade semi- synthetic heavy duty diesel engine oil formulated with high quality synthetic base oils and high performance additives for the lubrication of diesel engines of new generation heavy duty vehicles, ensures effective protection and high performance on heavy duty diesel engines.

PROPERTIES

- **High Dispersant Feature and Fuel Economy:**It disperses impurities thanks to its dispersant property, which keeps the dirt inside and keeps the lubrication channels in the engine parts constantly clean and open. thus fuel saving is achieved.
- **High Thermal And Oxidation Stability:**Due to the antioxidant property, the oil aging is very slow, so the periods of the oil change is long.
- **Superior Resistance to Reduction:**Due to the semisynthetic structure, the oil reduction is minimal. The periods of the oil change is long.
- **Low Exhaust Emissions:**It is an environmentally friendly product thanks to its ability to reduce harmful exhaust gas emissions.
- **Superior Corrosion Protection:**It protects against engine rust and corrosion thanks to its corrosion inhibitor with a good film layer.

SPECIFICATIONS/ APPROVALS

API CI-4, CH-4, MACK EO-N, MAN M 3275; MB 228.3, Renault RLD-2; Volvo VDS-3, MTU TYPE 2, JASO DH-1, CUMMINS CES 20078

TECHNICAL SPECIFICATIONS

Test	Method	Typical Properties
Kinematic Viscosity (100°C, cSt)	ASTM D445	14,5
Viscosity Index	ASTM D2270	140
Flash Point (°C)	ASTM D92	224
Pour Point (°C)	ASTM D97	-36
Density (20°C, g/cm ³)	ASTM D 1298	0,880

*Typical values may vary slightly from production to production

XENOL ENERJİ SAN. VE TİC. A.Ş.



GEBKİM ihtisas OSB Nuri Türkler Caddesi No:4 Dilovası / KOCAELİ



+90 262 646 11 01



info@xenol.com



STORAGE

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

HEALTH AND SAFETY

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

XENOL ENERJİ SAN. VE TİC. A.Ş.



GEBKİM ihtisas OSB Nuri Türker Caddesi No:4 Dilovası / KOCAELİ



+90 262 646 11 01



info@xenol.com