

XENOL ANTIFREEZE G12 RED -40

Product Description and Field of Use

It is an ethylene glycol-based, ready-to-use red antifreeze with special organic type corrosion inhibitor, especially formulated for vehicles with radiators made of aluminum and its alloys. It is recommended for use in cold regions down to -40°C. It is suitable for use in gasoline and diesel engines. It is ready for direct use. Not recommended for use in regions colder than -40°C.

Properties and Benefits

- It can be used in all kinds of radiators in all seasons.
- Thanks to special anti-corrosion additives, it protects the copper and brass materials in the engine against corrosion and does not damage the gaskets.
- It prevents cracking and other damage caused by expansion in cold climates.
- Compatible with all sealing components.
- Does not contain nitrite, boron, phosphorus, silicate, amine
- It is ready for direct use.

Specifications and Approvals Fulfilled

TEST	TEST METHOD	TYPICAL VALUES
Apperance	-	Clear
Color	ASTM D 1122	Red
Boiling Point C	ASTM D 1120	118
PH Value	ASTM D 1287	7-11
Freezing Point C	ASTM D 1177	-40

* Değerler üretimden üretime farklılıklar gösterebilir.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.