

XENOL MARINE 30/20

Product Description and Field of Use

is a range of engine oils developed for use in medium speed diesel engines in marine propulsion and power generation applications. Formulated using high quality base oils, supersedes the previous by incorporating a unique formulation of additive technology systems designed to overcome the adverse conditions seen in low oil consumption engines operating with varying heavy fuel qualities.

Properties and Benefits

- Excellent anti-foam properties
- Tolerant to water contamination
- Cleans and protects the engine whilst performing well in used oil analysis trends (by improved ability to release dirt and water in purifier centrifuges)

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
SAE Number			30
Density, @15 °C	g/cm ³	ASTM 4052	0,90
K. Viscosity, @ 100°C	cSt	ASTM D 445	11,5
Viscosity Index		ASTM D 2270	108
Flashing Point	°C	ASTM D 92	200
Pour Point	°C	ASTM D 97	-6
Total Base Number, mg KOH/g	-	ASTM D2896	20

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/18.07.2022-05