

XENOL MARINE 40/15

Product Description and Field of Use

Xenol Marine 40/15 is high performance lubricants specifically developed for use in modern highly rated marine and power generation four-stroke engines operating on distillate fuels.

Properties and Benefits

- Long lasting protection in the toughest operating conditions
- Enhanced performance at high temperatures
- Potential to extend the time between overhauls so reducing costs
- Formulated for excellent engine cleanliness
- Cleaner piston ring zone
- Enhanced detergency, excellent thermal and oxidative stability
- Offers the potential to simplify and reduce overall lubricant usage
- High load carrying capabilities and high gear performance that 13,5 enables them to be used as a common oil for both engine and transmission systems.
- Reduced maintenance and wear

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
SAE Number			40
Density, @15 °C	g/cm ³	ASTM 4052	0,895
K. Viscosity, @ 100°C	cSt	ASTM D 445	13,5
Viscosity Index		ASTM D 2270	105
Flashing Point	°C	ASTM D 92	200
Pour Point	°C	ASTM D 97	-12
Total Base Number, mg KOH/g	-	ASTM D2896	15

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/18.07.2022-05