

XENOL MARINE 40/40

Product Description and Field of Use

It is used in large difficult areas made in heavy fuel burning engines. Use in the toughest high grade turbocharged medium speed diesel engines. Excellent in all performance demanding requirements from a truly high-quality lubricant.

Properties and Benefits

- Superior wear performance.
- Improved thermal & anti-oxidation stability.
- Tolerant to water contamination.
- Cleans and protects the engine whilst performing well in used oil analysis trends (by improved ability to release dirt and water in purifier centrifuges)

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0,913
K. Viscosity, @ 100°C	cSt	ASTM D 445	14,0
Viscosity Index		ASTM D 2270	105
Flashing Point	°C	ASTM D 92	>190
Pour Point	°C	ASTM D 97	-6
Total Base Number, mg KOH/g	-	ASTM D2896	40

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/18.07.2022-05