

XENOL RACE 4T 15W-40 SL/CF

Product Description and Field of Use

Is high performance conventional four-stroke motorcycle engine oils primarily intended for general use in all types of four-stroke motorcycles and engines.

Properties and Benefits

- Helps extend engine life
- Helps keep engines clean for smoother operation
- Protects critical engine components.
- Year-round engine protection and performance.
- Good corrosion protection
- Thermal and oxidation stability

Specifications and Approvals Fulfilled API SL/CF, JASO MA2,

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM 4052	0.85
K. Viscosity, @ 100°C	cSt	ASTM D 445	13,7
Viscosity Index		ASTM D 2270	130
Flashing Point	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-25

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37