

## XENOL ELITE 10W-30 SL/CF

### Product Description and Field of Use

XENOL ELITE 10W-30 SL/CF has been formulated with cleansin technology. It works harder to protect than ordinary motor oils by continuously preventing dirt and sludge build-up and reduce engine noise.

### Properties and Benefits

- Helps protect against the build up of damaging engine sludge.
- Formulated with cleansing technology.
- Helps reduce the oil volatility and therefore the oil consumption.
- Minimises vibratipn and engine noise.

### Specifications and Approvals Fulfilled

API SL/CF ACEA A2/B2

### Typical Properties\*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm <sup>3</sup>	ASTM 4052	0.862
K. Viscosity, @ 100°C	cSt	ASTM D 445	11,0
Viscosity Index		ASTM D 2270	155
Flashing Point	°C	ASTM D 92	228
Pour Point	°C	ASTM D 97	-35

\* Values may vary between productions.

### Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

### Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/18.07.2022-15