

## XENOL ATF DEXRON IV

### Product Description and Field of Use

It is a high performance universal ATF providing superior oxidation control, extended service intervals, maximum lows and highs year round. Provides temperature performance, improved fuel economy and skid stability..

### Properties and Benefits

- High performance at low temperatures thanks to its excellent viscosity.
- Thanks to its high oxidation resistance and thermal stability, it shows superior resistance to aging, ensures a long oil change period and reduces maintenance costs.
- Thanks to its special additives, it minimizes the wear that may occur in automatic gearboxes and extends the transmission life.
- Thanks to the special additives they contain, they prevent sediment formation and do not cause foaming. Provides protection against corrosion and corrosion.

**Specifications and Approvals Fulfilled** GM DEXRON®, DEXRON® II, II-E, III, III-G, III-H, VI • Ford MERCON®, MERCON® LV, Acura ATF-Z1, Audi 5 HP LT71141, Chrysler (Mopar) ATF-Plus, ATF +3, ATF +4, Allison C-3, C-4, TES-295, TES-389, CAT TO-2, Daewoo LT 71141, Esso LT 71141, BMW • Honda Z-1, Hyundai/Kia SP-II/III/IV, JASO, FIAT T-IV type, JWS 3309, Jaguar ATF 3403 M115, ATF LT71141, ZF 5HP24, ISUZU BESCO ATF-II /III, Mazda ATF D-II/M-III/M-V/FZ/S-1/N-1, MINI COOPER T-IV, Opel (all vehicles), Peugeot ZF 4HP20, Mercedes, Mitsubishi, Nissan/ Infinity Matic Fluids, Toyota ATF D-II/D-III/T-III/T-IV/WS, VW 5 HP, G-055-025 A2 (JWS 3309), Porsche ZF 5HP19FL, ZF 5HP20, LT71141, Saab T-IV, Scion (all vehicles), Shell 3403, M115, LA 2634, Subaru ATF, Suzuki ATF, Vickers M2950-S, I-286-S, Voith, Volvo CE 97340, ZF all 3 & 4

### Typical Properties\*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm <sup>3</sup>	ASTM 4052	0.85
K. Viscosity, @ 100°C	cSt	ASTM D 445	5,9
Viscosity Index		ASTM D 2270	148
Flashing Point	°C	ASTM D 92	226
Pour Point	°C	ASTM D 97	-45

\* Values may vary between productions.

### Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

### Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37