

XENOL READY TO USE ORGANIC ANTIFREEZE RED

Product Description and Field of Use

XENOL READY TO USE ORGANIC ANTIFREEZE RED does not contain nitrite, amine, phosphate, silicate, borate. It is a ready-to-use mono ethylene glycol based engine coolant. XENOL READY TO USE ORGANIC ANTIFREEZE RED provides long-term protection with its organic acid anti-corrosion package.

Properties and Benefits

- Provides superior protection against freezing, corrosion and overheating.
- Formulated using organic-based additives to be used in radiators of engines containing all kinds of materials, including aluminum.
- It can be used in all kinds of radiators in all seasons

Specifications and Approvals

SAE J 1034, TS 3582, BS 6580, ASTM D-3306, ASTM D-4985

Typical Properties*

| TEST | TEST METHOD | TYPICAL VALUES |
|------------------|-------------|----------------|
| Apperance | - | Clear |
| Density 20C | ASTM D 4052 | 1,08 |
| Boiling Point C | ASTM D 1120 | 108 |
| PH Value | ASTM D 1287 | 7,5-11 |
| Freezing Point C | ASTM D 1177 | -38 |

* Values may vary from production to production.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.