

XENOL CONCENTRATED SUPER ANTIFREEZE BLUE -78

Product Description and Area of Use

It is an ethylene glycol based product containing rust, corrosion, wear and antifoam additives to be used in engine radiators. It does not contain nitrites, amines and phosphates. It is suitable for use in gasoline and diesel engines. It lowers the freezing point of the coolant. By raising the boiling point of the water, it prevents the radiator water from boiling in summer. It prevents rust and corrosion in the cooling system.

Features and Benefits

- It can be used in all kinds of radiators in all seasons.
- Thanks to special anti-corrosion additives, it protects the copper and brass materyalse in the engine against corrosion and does not damage the gaskets.
- It prevents cracking and other damage caused by expansion in cold climates.
- Compatible with all sealing components.
- Does not contain nitrite, boron, phosphorus, silicate, amine

CERTIFICATES AND STANDARDS

SAE J 1034, TS 3582, BS 6580, ASTM D-3306, ASTM D-4985

Tipik Özellikler

Technical Specs	Metod	TYPICAL VALUES
Apperance	-	Clear
Color	ASTM D 1122	BLUE
Density ,@ 20 oC	ASTM 4052	1,1
Boilng Point C	ASTM D 1120	165
PH Value	ASTM D 1287	7,5-11
Freezing Point °C (%50)	ASTM D 1177	-37

* Values may vary from production to production..

MIXTURE RULER		
ANTIFREEZE	WATER	DEGREE OF PROT,°C
1 scale	1 scale	-37 °C
1 scale	1½ scale	-28°C
1 scale	2 scale	-18 °C

Storage conditions

It should be protected from direct sunlight and rain. Packaging should be stored tightly, under a porch or in a closed area. Storage temperature should be between (+5)- (+40)°C.

Health and Safety Information

Based on available information, this product is not expected to have adverse effects on human health when used in its intended location and under the specified conditions of use. Used product should not be burned or poured into soil or wastewater channels. Waste oils should be divided into categories according to the Regulation on the Control of Waste Oils

XENOL

LUBRICANTS

TEKNİK BİLGİ FORMU

and disposed of through licensed enterprises with the characteristics defined in this regulation. Please read the Material Safety Form when necessary..

+90 262 646 11 01 Pbx

 www.xenol.com

 info@xenol.com