

XENOL CONCENTRATED ORGANIC ANTIFREEZE RED-78

Product Description and Field of Use

It is a high quality, long-lasting coolant containing organic acid technology and ethylene glycol-based special additives, formulated to be used in the cooling systems of all gasoline and diesel engines in all seasons. It does not contain phosphate, nitrate and amine. It perfectly protects the engine's cooling system against freezing, boiling, corrosion, rust, cavitation, rust and abrasion. It does not evaporate at radiator temperature. In order to obtain perfect results, the cooling system must be clean and leak-free. It should be used by mixing with water. Only clean and clear water should be used.

Properties and Benefits

- Provides superior protection against freezing, corrosion and overheating.
- Formulated using organic-based additives to be used in radiators of engines containing all kinds of materials, including aluminum.

XENOL CONCENTRATED ORGANIC ANTIFREEZE RED-78 solution must be diluted with water in certain proportions before filling. Mixing ratios and freezing degrees are given below.

MIXTURE RULER		
ANTIFREEZE	WATER	DEGREE OF PROT,°C
1 scale	1 scale	-37 °C
1 scale	1½ scale	-28°C
1 scale	2 scale	-18 °C

Specifications and Approvals

TS 3582,MAN 324 Type NF, MB 325.0, ZF INTARDER, BMW N 600 69.0, AUDI TL 774-C, VW TL 774 C,PORSCHE 774 C, CAT SEBU 6250-12, MTU MTL 5048, JENBACHER, SKODA, SEAT, OPELTypical Properties

Typical Features

TEST	TEST METHOD	TYPICAL VALUES
Apperance	-	Clear
Density 20C	ASTM D 4052	1,1
Boilng Point C	ASTM D 1120	165
PH Value	ASTM D 1287	7,5-11
Freezing Point C (%50)	ASTM D 1177	-37

* Values may vary from production to production.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.