

## XENOL OUTBOARD 2T TC W3

### Product Description and Field of Use

It is a high-performance, two-stroke engine oil designed for many high-performance, water-cooled two-stroke outboard engines used in marine applications. It is formulated with high purity semi-synthetic base oils and an ashless dispersant additive system that provides superior protection against exhaust exhaust deposits, corrosion and wear. Spark plug contamination and premature ignition are also minimized, ensuring perfect operation..

### Properties and Benefits

- Good thermal and oxidation stability and deposit control.
- Exceptional wear protection.
- Excellent anti-corrosion properties.
- Reduces spark plug fouling and exhaust port deposits, thus minimizing premature ignition, extending spark plug and valve life and increasing fuel efficiency.

### Specifications and Approvals Fulfilled

API TC, NMMA TC-W3

### Typical Properties\*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm <sup>3</sup>	ASTM 4052	0,86
K. Viscosity, @ 100°C	cSt	ASTM D 445	8,8
K. Viskosite, @ 40°C	cSt	ASTM D 445	52,9
Akma Noktası	°C	ASTM D 97	-36

\* Values may vary between productions.

### Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

### Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.

XENOL/TDS/20.07.2022-37