#### **TECHNICAL DATA SHEET**

# **XENOL CERAMIX BLUE 10W-60 SN/CF**

#### **Product Description and Field of Use**

It is a synthetic engine oil designed for high-performance automobiles with atmospheric, compressed or turbocharged engines. It provides superior performance in new generation and modified vehicles with its synthetic structure and superior lubrication technology.

# **Properties and Benefits**

- The extra oil film thickness prevents the oil from burning in the combustion chamber and oil leaks.
- Anti-Engine Wear: Prevents engine wear during start-up.
- High Heat Oxidation and Foam Resistance: This product extends the oil life while providing a long oil change interval.
- It cleans the engine parts thanks to the detergent and dispersant it contains. Cleaner parts work better and provide better performance.
- Initial start-up is easy and extends the life of your engine even under lower temperatures.
- It protects the engine against wear at high temperatures and ensures that the engine remains within the initial production tolerances.

## **Specifications and Approvals Fulfilled**

API SN/CF, ACEA A3/B4, BMW M-Models, VW 501 01 / 505 00, MB 229.31 / 229.51

### Typical Properties\*

TEST	<u>UNIT</u>	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm <sup>3</sup>	ASTM 4052	0.851
	cSt	ASTM D 445	21.9-26.1
K. Viscosity, @ 100°C	CSI		
Viscosity Index		ASTM D 2270	165
Flashing Point	°C	ASTM D 92	240
Pour Point	°C	ASTM D 97	-36

<sup>\*</sup> Values may vary between productions.

## **Storage Conditions**

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

# **Health and Safety Information**

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.



