

XENOL CALCIUM BLUE GREASE 0-1-2-3

Product Description and Field of Use

It is a blue colored calcium-based grease suitable for general use, formulated with quality base oils, calcium soap and anti-corrosion components. Suitable for medium and high speed slip and roller bearings where temperature is not high. Suitable for medium and high speed bearings, low speed slip bearings and chassis applications where the operating temperature does not exceed 70°C.

Properties and Benefits

- Cohesion-enhancing chemicals in its formula increase the cohesiveness to metal and show excellent resistance to washing with water in humid and wet environments.
- Ensures effective protection against wear and corrosion thanks to its fibrous and water resistant structure.
- Helps to minimize maintenance costs with the effective protection it provides.

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES			
SOAP TYPE	g/cm ³	-	CA	CA	CA	CA
COLOR	cSt	-	BLUE	BLUE	BLUE	BLUE
NLGI		ASTM D 566	0	1	2	3
DROPPING POINT, °C, MIN	°C	ASTM D 217	80	85	90	90
WORKED PENETRATION 25 °C	°C	-	355-385	310-340	265-295	220-250

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to Regulation on Control of Waster Oils, and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Material Safety Sheet when necessary.