

XENOL ELITE MULTI 10W-40 SP

Product Description and Field of Use

Synthetic technology motor oil providing long-term protection against sludge and helping to keep gasoline and diesel engines clean and operating efficiently. It provides excellent sludge protection and helps to prevent engine wear. It is suitable for use in a wide variety of vehicles driven in demanding traffic conditions.

Properties and Benefits

- Helps protect against the build-up of damaging engine sludge.
- Helps control harmful deposits that may affect engine performance.
- Helps to extend engine life by providing effective protection against wear.
- Low oil consumption for less frequent top-up.

Specifications and Approvals Fulfilled

API SP, ACEA A3/B4, MB 226.5, MB 229.3, Renault RN0700/RN0710, VW 501 01/505 00, PSA B71 2300, Fiat 9.55535-D2

Typical Properties*

TEST	UNIT	TEST METHOD	TYPICAL VALUES
Density, @15 °C	g/cm ³	ASTM D4052	0.87
K. Viscosity, @ 100°C	cSt	ASTM D445	12.5-16.3
Viscosity Index	-	ASTM D2270	160
Flash Point	°C	ASTM D92	230
Pour Point	°C	ASTM D97	-35

* Values may vary between productions.

Storage Conditions

It should be protected from direct sunlight and precipitation. Packages should be stored in a sealed way, under a porch or in indoor areas. Storage temperature should be between (+5)-(+40)°C.

Health and Safety Information

In the light of the available information, this product is not expected to create a negative impact on human health when used in the intended location and under the specified conditions of use. Used product should not be incinerated or poured into soil and waste water channels. Waste oils should be sorted into categories according to the Regulation on Control of Waste Oils and disposed of via licensed enterprises having the properties defined in this regulation. Please read the Safety Data Sheet (SDS) when necessary.